



Product Specifications

Backrest

- Fixed rectangular shape with curvature design for the back.
- Inner panel shall be made of 13mm Thk. pressed plywood upholstered with High Resilience foam and covered with fabric / leatherette / leather.

Seat

- Rectangular shape with 'concave' design for better sitting comfort.
- Inner structure made of Ø21 tabular steel frame with metal strap attachment, integrated in High Resilience foams and fully upholstered with fabric / leatherette / leather.
- Removable by means of zipper.

Armrest, Panel & Leg Structure

- Armrest top constructed with 30mm wood thickness.
- Decorative aisle panel made of MDF board upholstered with padded cover.
- Centre and end standards are of lateral pedestal design made of 38 x 2.3mm Thk. square hollow section continuous welded to K-Roll Castor System.

Metal Finishing

- All metal parts exposed shall be stripped and cleaned with iron phosphate, hot water rinsed and then chromic acid rinsed.
- All metal parts are coated with an epoxy finish of at least 60 microns for indoor use.

Upholstery Material

- Refer to Ferco standard fabric / leatherette / leather charts.

Advantages

- Durability of the chair & after sales service for all spare parts of the model.
- Comfort especially studied according to fundamental criteria of ergonomic.

Fire Safety

- Fire Safety - Flammability compliance with California Bulletin 117 and international regulations in their last issues and particularly with safety regulations.

Warranty

- Refer to Ferco product warranty.

Options

- Round Seat Numbering
- Aisle Light with Illuminated Row Letter
- Embroidery logo
- Embroidery seat numbering
- A.D.A Panel
- Wooden outer back / seat outer
- Wooden / upholstered armrest
- Wooden panel
- Flammability compliance with BS 5852 : 2006 Section 3 Ignition Source 5

